



| Temps(s) | Gy(mm) |
|----------|-----------|
| 0,000000 | -289,0000 |
| 0,052333 | -290,0467 |
| 0,104667 | -291,0933 |
| 0,157000 | -292,1400 |
| 0,209333 | -293,1867 |
| 0,261667 | -294,2333 |
| 0,314000 | -295,2800 |
| 0,366333 | -296,3267 |
| 0,418667 | -297,3733 |
| 0,471000 | -298,4200 |
| 0,523333 | -299,4667 |
| 0,575667 | -300,5133 |
| 0,628000 | -301,5600 |
| 0,680333 | -302,6067 |
| 0,732667 | -303,6533 |
| 0,785000 | -304,7000 |
| 0,837333 | -305,7467 |
| 0,889667 | -306,7933 |
| 0,942000 | -307,8400 |
| 0,994333 | -308,8867 |
| 1,046667 | -309,9333 |
| 1,099000 | -310,9800 |
| 1,151333 | -312,0267 |
| 1,203667 | -313,0733 |
| 1,256000 | -314,1200 |
| 1,308333 | -315,1667 |
| 1,360667 | -316,2133 |
| 1,413000 | -317,2600 |
| 1,465333 | -318,3067 |
| 1,517667 | -319,3533 |
| 1,570000 | -320,4000 |

Position du centre d'inertie de la banquette 1 par rapport au faux plancher 0




Position relative de la pièce 3 par rapport à la pièce 4



| Temps(s) | Norme(mm) |
|----------|-----------|
| 0,000000 | 0,00000 |
| 0,052333 | 2,04544 |
| 0,104667 | 4,05477 |
| 0,157000 | 6,02330 |
| 0,209333 | 7,94596 |
| 0,261667 | 9,82229 |
| 0,314000 | 11,64653 |
| 0,366333 | 13,41761 |
| 0,418667 | 15,13415 |
| 0,471000 | 16,79542 |
| 0,523333 | 18,40131 |
| 0,575667 | 19,95226 |
| 0,628000 | 21,44918 |
| 0,680333 | 22,89337 |
| 0,732667 | 24,28647 |
| 0,785000 | 25,63035 |
| 0,837333 | 26,92706 |
| 0,889667 | 28,17877 |
| 0,942000 | 29,38789 |
| 0,994333 | 30,55606 |
| 1,046667 | 31,68608 |
| 1,099000 | 32,77992 |
| 1,151333 | 33,83364 |
| 1,203667 | 34,86724 |
| 1,256000 | 35,86461 |
| 1,308333 | 36,83352 |
| 1,360667 | 37,77564 |
| 1,413000 | 38,69252 |
| 1,465333 | 39,58662 |
| 1,517667 | 40,45626 |
| 1,570000 | 41,30569 |

Valeur du déplacement vertical de la banquette 1 :
 Longueur du vérin 3+4 en position banquette verrouillée :



Justification du choix de vérin
cas : Effort maxi du vérin 3+4 :

